

Wind indicator units for naval application



Illustration 1



Illustration 2



Illustration 3

In white and black...

moves the pointer on the ergonomically well readable scale. With reference to the ship's momentary values for wind direction are clearly and unambiguously interpretable (illustration 1).

Green-red segments for port and starboard support this function. The indicator (illustration 3) is a complete solution.

As indicator station for wind parameters two indicators each (e.g. illustration 1+2) can be combined into one panel.

- ▶ very reliable and long-term stable indicators
- ▶ white, dimmable scale illumination
- ▶ clearly interpretable and very well readable analogous scales
- ▶ standard housing for installation
- ▶ robust meters and scales
- ▶ high linearity

civil ships • container ships • marine

Example illustration - others on request.

Professional Naval-Line

Wind Indicators for ships

Code Id-No.	Wind direction WD (1476 Q144SBN18) 00.14763.300 023	Wind speed WS (1477 Q144SB) 00.14773.300 004	WD and WS (14763 Q144SBN18) 00.14763.311 442
Measuring element:	three-coil system • „electric shaft“	moving-coil meas. system	WD: „electric shaft“ • WS: digital voltmeter
Measuring range:	0...360° • analogue	0...120 kn • 0...25 kn • analogue	WD: 0...360° • analog WS: 0...120 kn • digital
Accuracy:	± 5°	± 2% FS	WD: ± 5° WS: ± 2% FS
Resolution/ Div. of scale:	≤ 10°/ 10°	≤ 1 kn/ 1 kn • ≤ 5 kn/ 5 kn	WD: ≤ 10°/ 10° • analog WS: 0.1 kn • dig. 3 1/2-digits
Input signal:	N18-potentiometer • 3 x 10 V	0...5.2 mA • R _i = 110 Ω	WD: N18-potentiometer 3 x 10 V • WS: 0...4 mA
Dimensions/ Weight:	144 x 144 x 130 mm • 2 kg	144 x 144 x 90 mm • 1.4 kg	144 x 144 x 130 mm • 3 kg
Housing:	standard housing for control panels • black scale • white inscription • lighted		
Supply voltage:	for lighting 24 V _{AC} • 4 W		
Connectable to:	WD/WS sensors e. g. (1455 HGN18) • (14513 HG4N18)* • SYNMET-DAC-module		
Included in delivery:	2 brackets		

* adaptation necessary