



OVERVIEW

A highly integrated multifunction calibrator featuring several patented technologies, ADT222 is an ultra-compact, rugged, and ease-to-use hand-held device for sourcing, simulating and measuring pressure, temperature, and electrical signals. Its smartphone-like menu and interface make the operation simpler and easier. ADT222 is ideal for calibrating, maintaining, and troubleshooting process instrumentation. Automation and documentation capabilities make the ADT222 a turnkey solution.

FEATURES

- Sourcing, simulating and measuring pressure, temperature and electrical signals
 - Sources and measures mV, mA, ohms, RTDs, thermocouples, frequency, and pulses
 - Simulates and measures 13 thermocouples, 11 RTDs, and pressure to calibrate transmitters
 - Measures and sources pressure using CDP series Intelligent Digital Pressure Modules from -15psi to 10,000 psi (-1bar to 700bar)
 - 24V loop power supply
 - Simultaneous dual reading capability
 - Automatic switch test
 - Supports square root transmitter
 - Pulse frequency output for the calibration of flow totalizer
- Easy to use
 - Smart phone-like menu and interface make the operation simpler and easier

- Ultra-compact, size 3.9" x 7.6" x 2.0" (100mm x 192mm x 52mm), and weight 1.6lb (0.7kg)
- One hand operation
- Calibrated cold junction compensation (Patented)
 - Cold junction equivalent block in the calibrator
 - A calibrated PRT element with flexible leads is installed in the equivalent block for thermocouple cold junction compensation
 - This PRT element can be pulled out from the calibrator and re-calibrated and corrected at ice point easily
- Built-in temperature read out
 - CVD coefficients of a calibrated PRT can be input into the calibrator for accurate temperature measurement.
- Documenting and automated procedure capability
 - Manage the information of the device under test
 - Set up automated calibration procedures, and ADT222 performs the test, calculates the errors, displays and / or stores the results in the memory, and highlights the out-of-tolerance points.
 - As-found and As-left functions allow recording and documenting results for quality control.
 - Download tasks and upload the results
 - Snapshots allow you to capture and save work
- Built-in unit conversion tool
 - Built-in converters for pressure units, temperature units, temperature vs. resistance (RTDs), and temperature vs. millivolt (thermocouples)
- Multilingual interface
 - English, Chinese, German, French, Italian, Spanish, Russian, Japanese.
- Display
 - 3.5 inch TFT color screen
- Rugged
 - Rugged design for harsh environments.
 - Passed a 1-meter drop test
 - Three years warranty for the ADT222, and one year for the battery pack
- Misuse protection
 - Up to 30V voltage on any two sockets and up to 1A current on current sockets will not damage the calibrator, and the calibrator will return to normal condition as soon as the voltage or current is removed.
- Rechargeable and replaceable battery
 - Rechargeable Li-ion battery for 15 hours uninterrupted use.
 - Battery life will be reduced when 24V is applied
 - The rechargeable battery is replaceable.

APPLICATIONS

The ADT222 multifunction calibrator is a process tool for measuring, sourcing and simulating mA, mV, V, RTDs, thermocouples, ohms, frequency, pulses and pressure, captures switch values and provides 24 V loop power.

Electrical

- Resistance measurement / simulation
- Voltage measurement / generation
- Current measurement / generation
- Frequency measurement / generation
- Pulse counting/generation
- 24 VDC loop supply
- Switch sensing

Temperature

- RTD measurement /simulation
- TC measurement /simulation

Pressure

- Gauge pressure measurement
- Absolute pressure measurement

SPECIFICATIONS

Electrical Specifications

Measurement Accuracy			
	Range	Resolution	Accuracy
Voltage DC	-75.0000 to 75.0000 mV	0.1 μ V	0.01%RD+0.005%FS
	-30.0000 to 30.0000 V	0.1mV	0.01%RD+0.005%FS
Current DC	-30.0000 to 30.0000 mA	0.1 μ A	0.01%RD+0.005%FS
Resistance	Two-wire 0 to 400.000 ohm	1 m Ω	0.02%RD+0.005%FS
	Three-wire 0 to 400.000 ohm	1 m Ω	0.02%RD+0.005%FS
	Four-wire 0 to 400.000 ohm	1 m Ω	0.01%RD+0.005%FS
	Two-wire 0 to 4000.00 ohm	10 m Ω	0.02%RD+0.005%FS
	Three-wire 0 to 4000.00 ohm	10 m Ω	0.02%RD+0.005%FS
	Four-wire 0 to 4000.00 ohm	10 m Ω	0.01%RD+0.005%FS
Frequency	1 to 50000.0 Hz	0.1Hz	0.005%RD+0.002%FS
Pulse	0 to 999999	1	N/A
Limit Switch	If the switch has detective voltage, its range is +3v to +24V		
Source Accuracy			
Voltage DC	-10.000 to 75.000 mV	1 μ V	0.02%RD+0.005%FS
	0 to 12.0000 V	0.1mV	0.02%RD+0.005%FS
Current DC	0 to 22.000 mA	1 μ A	0.02%RD+0.005%FS
Resistance	1 to 400.00 ohm	10 m Ω	0.02%RD+0.005%FS
	1 to 4000.0 ohm	100 m Ω	0.03%RD+0.01%FS
Frequency	0 to 50000.0 Hz	0.1Hz	0.005%RD+0.002%FS
Pulse	0 to 999999	1	N/A
DC24V	N/A	N/A	0.5V

Temperature Specifications

Thermocouple Measurement and Source Accuracy					
Measure and Simulate	Standard	Temperature Range (°C)	Accuracy (°C)		
				Measure	Source
S	IEC 584	-50 to 1768	-50 to 400	1.0	1.1
			400 to 1000	0.6	0.6
			1000 to 1768	0.7	0.8
R	IEC 584	-50 to 1768	-50 to 200	1.4	1.4
			200 to 500	0.6	0.6
			500 to 1768	0.6	0.7
B	IEC 584	0 to 1820	50 to 450	3.8	3.8
			450 to 800	0.9	0.9
			800 to 1820	0.7	0.7
K	IEC 584	-270 to 1372	-250 to -200	1.0	1.1
			-200 to -100	0.4	0.5
			-100 to 600	0.3	0.3
			600 to 1372	0.4	0.5
N	IEC 584	-270 to 1300	-250 to -200	1.5	1.6
			-200 to -100	0.5	0.6
			-100 to 1300	0.4	0.5
E	IEC 584	-270 to 1000	-250 to -200	0.6	0.7
			-200 to -100	0.3	0.3
			-100 to 0	0.2	0.2
			0 to 700	0.2	0.3
			700 to 1000	0.2	0.4
J	IEC 584	-270 to 1200	-210 to -100	0.3	0.3
			-100 to 1200	0.3	0.4
T	IEC 584	-270 to 400	-250 to -200	0.8	0.9
			-200 to 0	0.4	0.4
C	ASTM E988	0 to 2315	0 to 1000	0.5	0.5
			1000 to 1800	0.7	0.9
			1800 to 2315	1.0	1.4
D	ASTM E988	0 to 2320	0 to 100	0.5	0.5
			100 to 1100	0.4	0.5
			1100 to 2000	0.6	0.9
G	ASTM E1751	0 to 2315	2000 to 2320	0.9	1.3
			0 to 200	2.4	2.4
			200 to 400	0.5	0.5
L	DIN43710	-200 to 900	400 to 1400	0.4	0.5
			1400 to 2315	0.7	1.0
			-200 to -100	0.2	0.3
U	DIN43710	-200 to 600	-100 to 400	0.2	0.2
			400 to 900	0.2	0.3
			-200 to 0	0.4	0.4
			0 to 600	0.2	0.3

RTD Measurement and Source Accuracy						
Measure and Simulate	Standard	Temperature Range (°C)		Accuracy (°C)		
				Measure (2W/3W)	Measure (4W)	Source
Pt10(385)	IEC 751	-200 to 850	-100 to 200	0.65	0.60	0.65
			200 to 600	0.82	0.72	0.82
			600 to 850	0.96	0.82	0.96
Pt100(385)	IEC 751	-200 to 850	-100 to 200	0.15	0.1	0.15
			200 to 600	0.26	0.16	0.26
			600 to 1850	0.33	0.20	0.33
Pt100(3916)	IEC 751	-200 to 850	-100 to 200	0.15	0.10	0.15
			200 to 600	0.26	0.16	0.26
			600 to 850	0.33	0.20	0.33
Pt200(385)	IEC 751	-200 to 850	-100 to 200	0.37	0.32	0.69
			200 to 600	0.51	0.41	0.93
			600 to 850	0.61	0.48	1.08
Pt500(385)	IEC 751	-200 to 850	-100 to 200	0.20	0.16	0.36
			200 to 600	0.32	0.22	0.54
			600 to 850	0.40	0.27	0.67
Pt1000(385)	IEC 751	-200 to 850	-100 to 200	0.10	0.05	0.25
			200 to 600	0.2	0.10	0.42
			600 to 850	0.27	0.14	0.54
Cu10(427)	IEC 751	-100 to 260	-100 to 260	0.61	0.56	0.61
Cu50(385)	IEC 751	-50 to 150	-50 to 150	0.17	0.13	0.17
Cu100(385)	IEC 751	-50 to 150	-50 to 150	0.12	0.09	0.12
Ni120(672)	DIN 43760	-100 to 260	-100 to 260	0.07	0.05	0.07
Ni100(618)	DIN 43760	-100 to 260	-100 to 260	0.08	0.06	0.08

Pressure Specification

CDP series Pressure Modules are available for gauge, vacuum and absolute pressure from -15 psi to 10,000 psi (-1 bar to 700 bar). Accuracy from 0.025% FS includes operation over 14° F to 122° F (-10° C to 50° C), one year stability and calibration uncertainty. For detail specification refer to pressure modules datasheet.

General Specifications

Environmental Specifications	
Operating Temperature	-10° C to 50° C
Storage Temperature	-20° C to 60° C
Humidity	<90%, non-condensing

Safety Specifications	
European Compliance	CE Marked

Mechanical Specifications	
Display	3.5 inch TFT color screen
Electrical Connection	φ 4mm sockets and flat mini-jack thermocouple socket
Pressure connection	Pressure module connector
RS232 Interface	standard RS232 - DB9 socket
Size	3.9" x 7.6" x 2.0" (100mm x 192mm x 52mm)
Weight	1.6 lb (0.7 kg)
Power Supply	Polymer Li - ion rechargeable battery, or 10V DC adaptor
Battery	Rechargeable Li-ion battery (included)
Battery Life	15 hours uninterrupted use Battery life will be reduced when 24V is applied
Battery Charge	110V/220V external power adapter (included)

Ordering Information

Model Number: ADT223

Accessories (included)

100V/220V external power adapter	1pc
Chargeable Li-ion battery	1pc
Test leads	3 sets(6 pcs)
Short circuit cable	1 set(2 pcs)

Optional Accessories:

Model Number	Description
CDP	Pressure Modules
9060	Pressure module connection cable
9050	USB to RS232(DB-9Male) Adapter
9080	Cold junction compensation kits (including TC plug, compensation cable, S, R, B, K, N, E, J, T, C, D, G, L, U)
9712	Spare chargeable Li-ion battery for multifunction calibrator
9816	110V/220V external power adapter for multifunction calibrator
9906	Carrying case for multifunction calibrator
9510	Task management software for multifunction calibrator
9121-317A	NIM traceable calibration certificate for multifunction calibrator