

DIFFERENTIAL PRESSURE TRANSMITTERS

DPT-MOD Series

Differential pressure transmitter with Modbus communication and Input terminal

The DPT-MOD differential pressure transmitter for air conforms to Modbus over serial line protocol, using RTU transmission mode and RS485 interface. The digital output signal is sent over Modbus enabling the DPT-MOD to connect directly to a field communications network.

DPT-MOD requires less wiring than traditional 3-wire transmitters, since multiple devices can be connected on serial line.

The DPT-MOD includes an Input terminal that enables reading of multiple other signals such as temperature or control relays over Modbus. The Input terminal has two input channels designed to accept 0–10 V, ntc10k, Pt1000, Ni1000/(-LG), and BIN IN (potential free contact) signals. For example, DPT-MOD can read values from one differential pressure measurement point and two temperature measurement points. Hence, the DPT-MOD does the work of three transmitters.



SIMILAR PRODUCTS

- DPT-2W series differential pressure transmitters with 4–20 mA 2-wire configuration
- DPT-R8 series 8-range differential pressure transmitters
- DPI series electronic differential pressure switches
- PS series mechanical differential pressure switches
- DPT-FLOW series airflow transmitters

APPLICATIONS

DPT-MOD series devices are commonly used in HVAC/R systems for:

- fan, blower and filter monitoring
- pressure and flow monitoring
- valve and damper control
- pressure monitoring in cleanrooms

MODEL SUMMARY

	DPT-MOD-2500		DPT-MOD-7000	
Measurement ranges (Pa)	-250...2500		-250...7000	
Description	Model	Product code	Model	Product code
Differential pressure transmitter with Modbus configuration and display	DPT-MOD-2500-D	114.003.002	DPT-MOD-7000-D	114.009.002

DIFFERENTIAL PRESSURE TRANSMITTERS

DPT-MOD Series

Differential pressure transmitter with Modbus communication and Input terminal

SPECIFICATIONS

Performance

Accuracy (from applied pressure):
±1.5 % + 1 Pa
(Including: general accuracy, temperature drift, linearity, hysteresis, long term stability and repetition error)
Response time:
1...20 s selectable via menu
Max pressure:
400 kPa

Communication

Protocol: MODBUS over Serial Line
Transmission Mode: RTU
Interface: RS485
Byte format (11 bits) in RTU mode:
Coding System: 8-bit binary
Bits per Byte:
1 start bit
8 data bits, least significant bit sent first
1 bit for parity
1 stop bit
Baud rate: selectable in configuration
Modbus address: 1–247 addresses selectable in configuration menu
Zero point calibration options:
• Manual pushbutton autozero
• Via Modbus write coil
Response Time:
0.8 sec, 2.0 sec, or 10 sec selectable in configuration menu

Technical Specifications

Media compatibility:
Dry air or non-aggressive gases
Measuring units:
Selectable via menu (Pa, mbar, inchWC, mmWC, psi)
Measuring element:
Piezoresistive
Environment:
Operating temperature: -10...+50 °C
Storage temperature: -20...+70 °C
Humidity: 0 to 95 % rH

Physical

Dimensions:
Case: 102.0 x 71.5 x 36.0 mm
Weight:
150 g, with accessories 290 g
Mounting:
2 each 4.3 mm screw holes, one slotted
Materials:
Case: ABS
Lid: PC
Protection standard:
IP54
Display :
2-line display (12 characters/line)
Line 1: active measurement
Line 2: units

Electrical Connections:
4+3 spring load terminals, max 1.5 mm²
Cable Entry: M20
Pressure connections:
Male \varnothing 5,0 mm and 6,3 mm

Electrical

Supply voltage:
24 VAC or VDC ± 10 %
Power consumption:
< 1.3 W
Output signal:
via Modbus

Conformance

Meets requirements for CE marking:
EMC directive 2004/108/EC
RoHS Directive 2002/95/EC



How to generate a model?

Example:	Product Series		
	DPT-MOD-2500-D	DPT-MOD	Differential pressure transmitter with Modbus configuration
		Highest available measurement range	
	-2500	-250...2500 Pa	
	-7000	-250...7000 Pa	
		Display	
	-D	With display	
Model	DPT-MOD	-2500	-D