

DIGITAL OXYGEN INDICATOR

XO-326IIs

Digital oxygen indicator



Oxygen concentration



Galvanic cell sensor

5m Cable:  
XO-326IIsA  
XO-326IIsA-V  
(Vibration)



1m Spiral Cable:  
XO-326IIsB  
XO-326IIsB-V  
(Vibration)



10m Cable:  
XO-326IIsC  
XO-326IIsC-V  
(Vibration)  
XO-326IIsB-V  
(Vibration)



FEATURES

- About 15000 Hours of Continuous Use
- Automatic Air Adjustment
- Replaceable Sensor

SPECIFICATIONS

Model	XO-326IIsA XO-326IIsA-V	XO-326IIsB XO-326IIsB-V	XO-326IIsC XO-326IIsC-V
Cable Length	5m	1m (spiral cable)	10m
Target Gas	Oxygen		
Detection Principle	Galvanic cell		
Sampling Method	Diffusion Type		
Detection Range	0 to 25.0 vol%		
(Service Range)	(25.1 to 40.0%)		
Indication Accuracy	Within +/-0.5vol%		
Display Resolution	0.1 vol%		
Alarm Set Value	1st stage: 19.5 vol% 2nd stage: 18.0 vol%		
Response Time	Within 20 seconds		
Alarm Function	Buzzer sounds, Red lamp blinks, LCD display blinks (latching), Vibration (for vibration specifications)		
Power Source	2 x size AA alkaline battery (LR6/ made by PANASONIC)		
Continuous Use	Approx. 15,000 hours		
Explosion-proof Structure	Ex ia II CT3 X (Japan)		
Protection Class	IP20 or equivalent		
Operating Temperature/ Humidity	-10 to 40 degrees C 30 to 85% RH (non condensing)		
Dimensions (mm) (excluding protrusions)	66(W) x 170(H) x 29(D)	66(W) x 120(H) x 29(D)	66(W) x 200(H) x 29(D)
Weight	Approx. 340g	Approx. 265g	Approx. 410g

Conforms to JIS T 8201  
The Ship Equipment Inspection Society of Japan (HK) approved product  
(Designation required)